

1939E 5:4 PCAP

Open-Frame Touchscreen



Feature:

- + Metal shell, open frame structure
- + Flat and zero bezel appearance
- + Industrial grade LCD, LED backlight
- + Resolution 1280X1024@60Hz
- + 10 point projection capacitive touchscreen
- + Cover plate anti riot and anti fingerprint
- + Video interface: HDMI+VGA
- + Multiple assembly holes on the side and back
- + Support OS: Windows/Android/Linux
- + 3-Years warranty



Optional:







- No Touch
- Privacy Filter
- AG Coating
- Touch interface: RS232
- Video interface: Display Port



TDS1939E Open-Frame Touchscreen Specifications

Model	1939E
Color	Black/Silver
Diagonal	19''
Aspect Ratio	5:4
Active Area	376.32X301.06(mm)
Dimensions	420X349X42.2(mm)
Resolution	1280X1024@60Hz
Viewing Angle	Horizontal: 89°/89°,Vertical: 89° /89°
Number of Colors	16.7M
Brightness (typical)	LCD Panel: 300 nits,PCAP: 275 nits
Response Time	5ms
Contrast Ratio	1000:1
Touch Technology	CAP (Projected Capacitive) - 10 Touch
Transmittance	≥90%
Surface hardness	7H(Mohs)
Touch Interface	USB2.0
Video Interface	VGA+HDMI
Input Voltage	AC:100-240 VAC, 50/60 Hz
Sealability	Touchscreen sealed to bezel
Drop Test	1kg steel ball falls from 1.2m without breaking
Weight (Unpackage)	5KG
Shipping Dimensions	570X400X145(mm)
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Humidity	Operating: 20% to 70%; Storage: 10% to 80%
Mounting Options	Back VESA two groups of holes: 75mm&100mm Four sides has a set of fixing holes: 142mm
MTBF	50,000 hours demonstrated
Power Supply	DC:12V3A
Warranty	3-years
Agency Approvals	FCC, CE, ROHS
Support OS	Windows/Linux\Android
What's in the Box	1*USB cable,1*VGA cable,1*DC cable (Standard) L'' (Side Mount) Brackets and w/Screws (Options)

TDS1939E-PCAP



Dimensions are in millimeters

