## **2439C 16:9 PCAP**

## Open-Frame Touchscreen



## **Features**

- + Metal shell, open frame design
- + Flat and zero bezel appearance
- + Commercial grade LCD, LED backlight
- + Resolution 1920X1080 FHD@60Hz
- + High contrast and full viewing Angle
- + Supports vertical and horizontal
- + 10 point projection capacitive touchscreen
- + Cover plate anti riot and anti fingerprint
- + Removable OSD remote for easy use
- + Video interface: HDMI+VGA
- + Multiple fixed holes on the side and back
- + Support OS: Windows/Android/Linux
- + 3-years Warranty



- No Touch
- Privacy Filter
- AG Coating
- Touch interface:RS232
- Video interface: Display Port





TDS2439C Open-Frame Touchscreen Specifications	
Model	2439C
Diagonal	23.8"
Color	Black/Silver
Aspect Ratio	16:9
Active Area	527.04mmX296.49mm
Dimensions	569.6X341.6X49.9 (mm)
Resolution	1920X1080FHD@60Hz
Viewing Angle	Horizontal: 89° /89°; Vertical: 89° /89°
Number of Colors	16.7M
Brightness	LCD panel: 250nits; PCAP: 225 nits
Contrast Ratio	3000: 1
Response Time	10ms
Touch Technology	PCAP (Projected Capacitive) - 10 Touch
Input method	Finger, Capacitance pen(Standard)
	Latex gloves touch (pre commissioning required)
Transmittance	$\geq 90\%$
Surface hardness	7H(Mohs)
Touch Interface	USB 2.0
Video Interface	HDMI + VGA
Input Voltage	AC: 100-240 VAC,50/60 Hz
Sealability	Touchscreen sealed to bezel
Drop test	1kg steel ball falls from 1.2m without breaking
Weight	6.9KG
Shipping Dimensions	720 X450 X160(mm)
Operating Temperature	0°C-40°C
Storage Temperature	-20°C-60°C
Humidity	Operating: 20%-70%; Storage: 10%-80%
Mounting Options	VESA Hole on the back: 100mm&200 mm
	Four sides has a set of fixing holes: 200mm
MTBF	30,000 hours demonstrated
Power Supply	DC:12V3A
Warranty	3-years
Agency Approvals	FCC; CE; RoHS
Support OS	Windows/Android/Linux
What's in the Box	1*USB cable,1*HDMI cable,1*DC cable,1*RJ45 OSD Remote (Standard) L" (Side Mount) Brackets and w/Screws (Options)

