

TDS2702E 16:9 PCAP

Curved touchscreen Monitor



Feature:

- + Innovative curved surface design
- + All-aluminum body, narrow and thin frame
- + The R1500 is curved comfort experience
- + Colorful magic light bar dynamic display
- + Resolution 1920X1080FHD@60Hz
- + 10-touch Projection Capacitive Touchscreen
- + Video interface: HDMI+VGA
- + Supports standard VESA wall mounting
- + Support OS: Windows/Android/Linux
- + 2-Year warranty



Optional:

- No Touch
- No light bar
- All-in-one(Android)
- Multi-light strip (Supports up to 8 light strips)



Curved touchscreen Monitor Specifications

Model	2702E
Diagonal	27"
Aspect Ratio	16:9
Physical shape	Curved, R1500
Display area	597.2 × 336.2 (mm)
Dimensions	664.6x397.2x95(mm)
Resolution	1920X1080FHD@60Hz
Viewing Angle	Horizontal: 89° /89°; Vertical: 89° /89°
Number of Colors	16.7M
Brightness (typical)	LCD panel : 300nits; PCAP : 255nits
Contrast Ratio	1200:1
Touch Technology	PCAP (Projected Capacitive Touchscreen)
Number of Touches	10-touch
Surface treatment	Hot Bending Process (Physics)
TP thickness	2.55mm(±0.3mm)
Transmittance	≥85%
Response time	10ms
Touch Interface	1*USB 2.0
Video Interface	1*VGA,1*HDMI
Light bar Interface	Option(Calling the debug interface)
Speaker	Option
Control	Display: OSD
	Light bar: Remote
Input voltage range	100-240 VAC,50/60 Hz
Power supply	DC: 12V5A(5.5*2.1)
Temperature	Operating: 0°C ~ 40°C, Storage:-20°C to 60°C
Humidity	Operating: 20% to 70%; Storage: 10% to 80%
MTBF	50,000 hours demonstrated
Mounting Options	VESA two groups of holes:75mm&100mm
Weight	Packaged:12KG
Packing Dimension	775X520X150(mm)
What's in the Box	1*1.8m USB cable,1*1.8m HDMI cable,1*1.8m DC cable 1*Power adapter, 1*Remote(option)
Agency Approvals	FCC, CE, ROHS

■ Product dimensions (mm)

